

## Force 400 Series


| Technical Specifications                     |        | EN 60118-0<br>Ear Simulator | EN 60118-7:2005<br>2ccm-coupler |
|----------------------------------------------|--------|-----------------------------|---------------------------------|
| <b>Output (OSPL90)</b>                       |        |                             |                                 |
| Max                                          | dB SPL | 121                         | 113                             |
| HFA Avg (1000,1600,2500 Hz)                  | dB SPL | 115                         | 108                             |
| <b>Gain (FOG50)</b>                          |        |                             |                                 |
| Max                                          | dB     | 52                          | 43                              |
| HFA Avg (1000,1600,2500 Hz)                  | dB     | 43                          | 36                              |
| <b>Reference Test Gain (Input 60 dB SPL)</b> | dB     | 38                          | 30                              |
| <b>EQ Input Noise</b>                        | dB SPL | 25                          | 24                              |
| <b>Frequency Response (RESP60)</b>           |        |                             |                                 |
| Low Frequency Limit                          | Hz     | 100                         | 100                             |
| High Frequency Limit                         | Hz     | 7100                        | 6700                            |
| <b>Total Harmonic Distortion</b>             |        |                             |                                 |
| 500 Hz (Input 70 dB SPL)                     | %      | 0,7                         | 0,7                             |
| 800 Hz (Input 70 dB SPL)                     | %      | 0,9                         | 0,9                             |
| 1600 Hz (Input 65 dB SPL)                    | %      | 0,8                         | 0,6                             |
| <b>Telecoil Sensitivity (MASL)</b>           | dB SPL |                             |                                 |
| <b>Battery (1000 Hz / Input 65 dB)</b>       |        |                             |                                 |
| Battery Current                              | mA     | 1,18                        | 1,16                            |
| Battery Life (Average)                       | Hour   | 77                          | 78                              |
| <b>Battery Type</b>                          |        | 10                          |                                 |
| <b>Operating Voltage</b>                     | V      | 1,3                         |                                 |
| <b>EQ Bands</b>                              |        | 49                          |                                 |
| <b>Number of programs</b>                    |        | 8                           |                                 |
| <b>WDRC channels</b>                         |        | 16                          |                                 |
| <b>Number of frequency channels</b>          |        | 49                          |                                 |
| <b>Microphone</b>                            |        | 1                           |                                 |
| <b>Telecoil</b>                              |        | Optional                    |                                 |
| <b>Volume control</b>                        |        | Multifunctional (Optional)  |                                 |

## CIC


## Force 400 IIC




### Fitting Range



### EN 60118-0 Ear Simulator



### EN 60118-7:2005 2ccm-coupler



### Programming System

Cable : ITE cable 10 Batt./Right&Left  
 Battery : Without Battery  
 Progr.-Box : Hi-Pro / Hi-Pro2 with USB  
 Software : CorrectFit2

Programming Cable

HI-PRO2



### Performance Features

#### Extra safety and durability tests:

- Ear-technic hearing devices are reliable, durable and robust with its unique design.
- CIC device is tested in according to IEC 60068-2-64 (Vibration)
- IEC 60068-2-31 (mechanical shocks)
- IEC 60068-2-14 (shock temperature changes)

Note: The tests are performed on the kit.

### Key Features:

- 80 Compression Application Parameters
- 49 Frequency Channels
- 24 kHz Sampling Frequency
- 16 MPO Limits
- 49 EQ Bands
- Up to 12 kHz Fitting Bandwidth\*
- 8 Programs
- 16 WDRC Channels
- (T-FIS) Tinnitus Frequency Isolation System (Static and Dynamic)
- Environment Classification
- Noise Reduction
- FBC (Super FeedBack Canceller)
- Program Change Warning (Voice or Tone)
- Low Battery Warning (Voice or Tone)
- Volume Control
- Starting Program/Volume Memory
- Data Logging
- Activation Delay
- Fitting Formula Settings (NAL-NL2, DSL Adult/ Pediatrics)
- Frequency Channel and WDRC Channel Independent Adaptation

\* Bandwidth is available in Gain Adjustments in Fitting software.

\* OSPL (Output Sound Pressure Level) - RESP (Frequency Response) - FOG (Full On Gain)

\* Technical datas are given in according to EN 60118-0 Ear Simulator (MZ coupler) / EN 60118-7:2005 2ccm-coupler values.